


#### Datasheet, technical data

# **General Characteristics**


Model number (on compressor nameplate)		MTZ32JF4BVE
Code number for Singlepack*		MTZ32-4VI
Code number for Industrial pack**		MTZ32-4VM
Drawing number		8501025f
Suction and discharge connections		Rotolock
Suction connection		1-1/4 " Rotolock
Discharge connection		1 " Rotolock
Suction connection with supplied sleeve		5/8 " ODF
Discharge connection with supplied sleeve		1/2 " ODF
Oil sight glass		Threaded
Oil equalisation connection		3/8" flare SAE
Oil drain connection		None
LP gauge port		Schrader
IPR valve		30 bar / 8 bar
Cylinders	1	
Swept volume	53,86 cm3/rev	
Displacement @ Nominal speed	9.4 m3/h @ 2900 rpm - 11.3 m3/h @ 3500 rpm	
Net weight	24 kg	
Oil charge	0,95 litre, POE - 160PZ	
Maximum system test pressure Low Side / High side	25 bar(g) / 30 bar(g)	
Maximum differential test pressure	30 bar	
Maximum number of starts per hour	12	
Refrigerant charge limit	2,5 kg	
Approved refrigerants	R404A, R507A, R134a, R407C	

#### **Dimensions**



D=224 mm H=356 mm H1=263 mm H2=68 mm

### Terminal box



#### **Electrical Characteristics**

Nominal voltage	380-400V/3/50Hz - 460V/3/60Hz
Voltage range	340-440 V @ 50Hz - 414-506 V @ 60Hz
Winding resistance (between phases) +/- 7% at 25°C	6.15 #
Maximum Continuous Current (MCC)	8 A
Locked Rotor Amps (LRA)	25 A
Motor protection	Internal overload protector

Recommended Installation torques

Oil sight glass	50 Nm
Power connections / Earth connection	Nm / 2 Nm
Mounting bolts	15 Nm

### Parts shipped with compressor

Mounting kit with grommets, bolts, nuts, sleeves and washers

Suction & Discharge solder sleeves, rotolock nuts and gaskets (shipped with rotolock version only)

Initial oil charge

Installation instructions

Approvals: CE certified, UL certified (file SA6873), CCC certified

\*Singlepack: Compressor in cardboard box

\*\*Industrial pack: 12 Unboxed compressors on pallet (order per multiples of 12)



2: Earth M4-12

1:

Spade connectors 1/4" Knock-out Ø 21 mm (0.83") 3:

4: Hole Ø 21 mm (0.83")



Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alternations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss, the Danfoss logotype and Maneurop are trademarks of Danfoss A/S. All rights reserved.





# Datasheet, accessories and spare parts

# Maneurop reciprocating compressor, MTZ032-4

Rotolock accessories, suction side	Code no.	
Solder sleeve, P09 (1-1/4" Rotolock, 5/8" ODF)	8153011	
Angle adapter, C09 (1-1/4" Rotolock, 5/8" ODF)	8168009	
Rotolock valve, V09 (1-1/4" Rotolock, 5/8" ODF)	8168033	Gaskets, sleeves and nuts
Gasket, 1-1/4"	8156131	
Rotolock accessories, discharge side	Code no.	
Solder sleeve, P06 (1" Rotolock, 1/2" ODF)	8153007	
Angle adapter, C06 (1" Rotolock, 1/2" ODF)	8168007	
Rotolock valve, V06 (1" Rotolock, 1/2" ODF)	8168031	( Car )   (C
Gasket, 1"	8156130	1 2 3
Rotolock accessories, sets	Code no.	1: Gasket
Angle adapter set, C09 (1-1/4"~5/8"), C06 (1"~1/2")	7703012	2: Solder sleeve
Valve set, V09 (1-1/4"~5/8"), V06 (1"~1/2")	7703005	3: Rotolock nut
Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black & white	8156009	
Oil / lubricants	Code no.	
POE lubricant, 160PZ, 1 litre can	7754019	
POE lubricant, 160PZ, 2 litre can	7754020	


Crankcase heaters	Code no.	Mounting l
PTC heater 27W,CE mark, UL	120Z0459	
Dolf tyme analysess bacton 54 W 220 V CE monty III	7772106	1

The heater 27 W,CE mark, CE	12020437
Belt type crankcase heater, 54 W, 230 V, CE mark, UL	7773106
Belt type crankcase heater, 54 W, 400 V, UL	7773013

Miscellaneous accessories	Code no.
Electronic soft start kit, MCI 15 C	7705006
Acoustic hood for 1 cylinder compressor	120Z0471
Oil equalisation nut	8153127

Spare parts	Code no.	
Mounting kit for 1 and 2 cylinder compressor, including 3 grommets, 3 bolts	8156001	
Oil sight glass with gaskets (black & white)	8156019	
Gasket for oil sight glass (black chloroprene)	8156145	
Service kit for terminal box 80 x 96 mm, including 1 cover 1 clamp	8156134	

# Mounting kit



1: Bolt (3x)

2: Lock washer (3x)

3: Flat washer (3x) 4: Sleeve (3x)


5: Grommet (3x)

6: Nut (3x)

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alternations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss, the Danfoss logotype and Maneurop are trademarks of Danfoss A/S. All rights reserved.







Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alternations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss, the Danfoss logotype and Maneurop are trademarks of Danfoss A/S. All rights reserved.

