

Electric to Pneumatic Transducer and Enclosures

The AO-P transducer converts an electronic signal into a linear pneumatic signal for the accurate positioning of valve and damper actuators typically used in heating and air conditioning systems. The transducer is available in two different mounting styles: Remote Mount with its own integral enclosure and conduit connection; or Panel Mount for mounting in control cabinet applications. The transducer includes provisions for manual override, and does not require calibration.



Figure 1. AO-P Transducer - Remote Mount.

Features

- Insensitive to vibration and mounting position to allow mounting directly on equipment and give stable performance
- Hand-Auto switch and override dial allow for manual control of output pressure for troubleshooting and emergencies
- Optional electrical connections to remotely monitor Hand-Auto switch position and output pressure
- Accurate and repeatable output pressure signal
- Easy to install, no setup or calibration is required
- The unit can be mounted directly on the wall or equipment without an additional enclosure to reduce cost
- Factory installed 0 to 30 psi (0 to 207 kPa) gauge is included
- High capacity, non-bleed device.



Figure 2. AO-P Transducer - Panel Mount.

Specifications

Supply Voltage	19 to 26 Vac (24 Vac typical)	Air Consumption for Compressor	10 SCIM (164 SCCM)
Power Consumption	1 VA	Tubing Connection	2 ea. 1/4" (6 mm) O.D. nominal, barbed fittings
Input Signal/Impedance	0 Vdc to 10 Vdc/20 K Ω 180 Ohms for 4-20 mA	Conduit Connections	Remote mount model has 2 ea. 1/2" (12.7 mm) conduit connections
Output Signal	0 to 20 psig (0 to 138 kPa) for 0 to 10V input 3 to 15 psig (20 to 103 kPa) for 4 to 20 mA input	Operating Temp.	32°F to 185°F (0°C to 85°C)
Output Capacity	500 SCIM (8.2 SLPM) minimum @ 5 psi (34.5 kPa) Drop (20 psi input, 15 psi output)	Operating Humidity	95% RH maximum (non-condensing)
Overall Dimensions:		Storage Temperature	-40°F to 185°F (-40°C to 85°C)
Remote Mount	4-1/4" H x 7-1/4" W x 3-1/16" D (108 mm x 184 mm x 78 mm)	Agency Listing	FCC Compliant
Panel Mount	4-1/4" H x 5-3/4" W x 3-1/16" D (108 mm x 146 mm x 78 mm)	Override Controls	The AO-P Transducer provides a continuous variable output override (the override does not function without power).
Output Accuracy	@ 77°F (25°C) \pm 0.50 psig (1.72 kPa) Max. 32°F to 122°F (0°C to 50°C) \pm 0.50 psig (3.45 kPa) Max. 122°F to 185°F (40°C to 85°C) \pm 1.0 psig (6.90 kPa) Max.	Override Monitoring Hand Auto	The AO-P Transducer provides a dry contact to indicate the position of the Hand-Auto Switch to an external device.
Output Repeatability	0.1 psig (0.7 kPa) Max. (Includes Hysteresis)	Hand-Auto Override Dry Contact Rating	0.3A, Class 2 Voltage
Air Supply Pressure	20 psig (138 kPa) absolute minimum (must be 5 psig minimum above maximum output) 30 psig (207 kPa) maximum safe pressure (oil-free and dry)	Override Monitoring Output Pressure	The AO-P Transducer provides an optional signal to monitor output pressure. Accuracy is \pm 0.25 psig (1.72 kPa) @ 77°F (25°C).
		Feedback Voltage Output	0-5 VDC = 0-20 p.s.i.

Product Ordering Information

Description	Product Part Number
AO-P Transducer - Remote Mount	545-208
AO-P Transducer - Panel Mount	545-113

Information in this document is based on specifications believed correct at the time of publication. The right is reserved to make changes as design improvements are introduced. APOGEE and Insight are registered trademarks of Siemens Building Technologies, Inc. Other product or company names mentioned herein may be the trademarks of their respective owners. © 2009 Siemens Building Technologies, Inc.