SIEMENS

Technical Specification Sheet Document No. 149-919 August 26, 2009



Immersion Well Temperature Sensors

Description

The Immersion Well Temperature Sensors monitor and transmit changes in temperature to the building control system. Specific devices within the range are compatible with whatever North American manufactured building automation system you may be installing. They thread into a well in a pipe and sense the medium temperature in the pipe. All sensors incorporate precision temperature sensing elements to accurately and reliably measure temperature.

Features

- Variety of sensing elements
- Suitable for hot or chilled medium
- Responsive to temperature change
- Accurate and reliable indication of temperature
- Familiar installation requires no special tools

Specifications

opeemedions		
Temperature Range	Controller dependent	
Output Signals	Changing resistance	
Sensing Element Type	ment Type NTC Thermistor, Platinum RTD, or Nickel RTD	
Accuracy		
NTC Thermistors, mid-range	±1.0°F (±0.5°C)	
Pt RTD and Ni RTD, mid-range	±0.75°F (±0.4°C)	
Installation		
Wiring	2-conductor: 18 to 22 AWG twisted pair (per code requirements)	
Calibration Adjustments	NTC: None required	
	RTD: Adjust for increased temperature offset (a constant) as required, related to added resistance of the field wiring	
External Installation Threads	1/2-inch – 14 NPT	
Conduit Connection Threads	1/2-inch – 14 NPSMI	
Housing Material	Cast zinc	
Immersion Well Material	300 Series Stainless Steel	

Figure 1. Immersion Well Temperature Sensor.

Immersion Well Temperature Sensor Product Numbers

Product Number	Description
QAE2012.005	Immersion Temperature Sensor, Metal Housing, Platinum 1000 Ohm, 385 Alpha, 2.5" Probe
QAE2012.010	Immersion Temperature Sensor, Metal Housing, Platinum 1000 Ohm, 385 Alpha, 4" Probe
QAE2012.015	Immersion Temperature Sensor, Metal Housing, Platinum 1000 Ohm, 385 Alpha, 6" Probe
QAE2020.005	Immersion Temperature Sensor, Metal Housing, Nickel 1000 Ohm, SIEMENS, 2.5" Probe
QAE2020.010	Immersion Temperature Sensor, Metal Housing, Nickel 1000 Ohm, SIEMENS, 4" Probe
QAE2020.015	Immersion Temperature Sensor, Metal Housing, Nickel 1000 Ohm, SIEMENS, 6" Probe
QAE2021.005	Immersion Temperature Sensor, Metal Housing, Nickel 1000 Ohm, JCI, 2.5" Probe
QAE2021.010	Immersion Temperature Sensor, Metal Housing, Nickel 1000 Ohm, JCI, 4" Probe
QAE2021.015	Immersion Temperature Sensor, Metal Housing, Nickel 1000 Ohm, JCI, 6" Probe
QAE2030.005	Immersion Temperature Sensor, Metal Housing, NTC 10K Ohm TYPE 2, 2.5" Probe
QAE2030.010	Immersion Temperature Sensor, Metal Housing, NTC 10K Ohm TYPE 2, 4" Probe
QAE2030.015	Immersion Temperature Sensor, Metal Housing, NTC 10K Ohm TYPE 2, 6" Probe
QAE2032.005	Immersion Temperature Sensor, Metal Housing, NTC 10K Ohm TYPE 3, 2.5" Probe
QAE2032.010	Immersion Temperature Sensor, Metal Housing, NTC 10K Ohm TYPE 3, 4" Probe
QAE2032.015	Immersion Temperature Sensor, Metal Housing, NTC 10K Ohm TYPE 3, 6" Probe

Accessories Ordering Information

Descript	lion	Part Number
Immer -sion Wells	2.5 in. (64 mm)	AQE2000.005
	4 in. (100 mm)	AQE2000.010
	6 in. (153 mm)	AQE2000.015
Immersion Well Repair Kit	PT 1000 Ohm (385 α)	AQE2012
	Ni 1K Ohm, Siemens	AQE2020
	Ni 1000 Ohm, JCI	AQE2021
	NTC 10K Ohm Type II	AQE2030
	NTC 10K Ohm Type III	AQE2032

Repair kits have components to fill any of the three Immersion Wells offered.

Information in this document is based on specifications believed correct at the time of publication. The right is reserved to make changes as design improvements are introduced. Product or company names mentioned herein may be the trademarks of their respective owners. © 2009 Siemens Building Technologies, Inc.