

QPA20... Series Room Air Quality Sensors

Description

The QPA20... series room air quality sensors optimize room comfort by enabling demand-controlled ventilation. The sensors can acquire: CO₂ and volatile organic compound (VOC) concentrations, relative humidity, and temperature. Models are available for CO₂, CO₂/VOC, CO₂/T, and CO₂/T/RH.

The sensor evaluates the CO₂/VOC concentrations and transforms it to a 0 to 10 Vdc linear proportional output signal.

For models with humidity, a capacitive humidity sensing element changes capacitance as a function of the relative humidity. An electronic measuring circuit converts the humidity signal to a continuous 0 to 10 Vdc signal that corresponds to a relative humidity range of 0 to 100%. For models with temperature, the sensor acquires room temperature with a sensing element that changes electrical resistance as a function of the temperature. The resistance is converted to an active 0 to 10 Vdc output signal that corresponds to a temperature range of 32°F to 122°F (0°C to 50°C) or -31°F to 95°F (-35°C to 35°C).

Sensors with an LCD window display the following measured values:

- CO₂ in ppm
- CO₂ and VOC as a bar chart (4 bars ≈ 2V, 20 bars ≈ 10V)
- Temperature in °C or °F
- Relative humidity in %

The wall-mounted sensors are suited for use with all systems and devices capable of acquiring and handling a 0 to 10 Vdc output signal.

Features

- Multisensor for CO₂/VOC, temperature, and humidity-temperature
- Maintenance-free infrared CO₂ sensing element, VOC sensing element based on a heated tin dioxide semiconductor
- 24 Vac operating voltage, 0 to 10 Vdc output signals



QPA20... Series Room Air Quality Sensor.



QPA20... Series Room Air Quality Sensor with Display.

General Specifications

Power Supply:

Operating voltage (SELV): 24 Vac \pm 20%
 Frequency: 50/60 Hz
 Power consumption: \leq 2 VA

Electrical:

Screw terminals: 2 \times 16 AWG or 1 \times 14 AWG

Environmental:

Temperature

Operating: 23°F to 113°F (-5° to 45°C)
 Storage: -13°F to 158°F (-25° to 70°C)

Humidity:


Operating: 0 to 95% rh (noncondensing)
 Storage: <95% rh

Physical:

Mounting: In 2 \times 4 inch (5 \times 10 cm) electrical conduit box

Weight in lb (kg):

Without display: 0.22 lb (0.10 kg)
 With display: 0.26 lb (0.12 kg)



Dimensions in Inches (mm).

Product Numbers and Specifications

Product Number	Specification						
	QPA2000	QPA2002	QPA2002D	QPA2060	QPA2060D	QPA2062	QPA2062D
CO ₂ measuring range: 0 to 2000 ppm Accuracy: \leq \pm 50 ppm +2% of measured value Output signal: 0 to 10 Vdc, linear Recalibration free: 8 years	•	•	•	•	•	•	•
VOC sensitivity: Low (R1), Normal (R2), High (R3)		•	•				
Temperature measuring range (slope and intercept): R2 and R3: 32°F to 122°F (0°C to 50°C) R1: -31°F to 95°F (-35°C to 35°C) Temperature measuring element: QPA2060: PT1000 QPA2062: NTC 10 k Ω Measuring accuracy in the range of: -31°F to 59°F (-35°C to 15°C): \pm 1K 59°F to 95°F (15°C to 35°C): \pm 0.8K 95°F to 122°F (35°C to 50°C): \pm 1K				•	•	•	•
Humidity range of use: 0 to 95% rh (noncondensing) Humidity measuring range: (slope and intercept) 0 to 100% rh Measuring accuracy at 73°F (23°C), 24 Vac: 0 to 30% rh: \pm 5% rh 30 to 70% rh: \pm 3% rh 70 to 95% rh: \pm 5% rh						•	•
Display (LCD) of measured value			•	•			•

Ordering Information

UNIVERSAL SENSOR PROGRAM			Q	P	A	2	0	x	x	x
TYPE	SENSOR	Q								
MEASURING FAMILY	CO ₂ /VOC	P								
APPLICATION/LOCATION	ROOM	A								
SENSOR TYPE	CO ₂	2								
HOUSING TYPE	CO ₂ HOUSING	0								
TEMPERATURE OUTPUT SIGNAL	NONE	0								
	0 TO 10 VOLT	6								
RH SIGNAL PRESENT										
CO ₂ OR VOC ONLY:	0 TO 10 VOLT	0								
CO ₂ /VOC AND RH:	0 TO 10 VOLT	2								
SEPARATOR										
FEATURE DESCRIPTION - ROOM TYPES										
	WITHOUT DISPLAY	<BLANK>								
	WITH LCD DISPLAY	D								

Information in this document is based on specifications believed correct at the time of publication. The right is reserved to make changes as design improvements are introduced. Other product or company names mentioned herein may be the trademarks of their respective owners.
 © 2007 Siemens Building Technologies, Inc.